

MP C2003SP	MP C2503SP	MP C3003SP	MP C3503SP	MP C4503SP	MP C5503SP	MP C6003SP
<b>GENERAL</b>						
Warm up time:	19 sec	19 sec	19 sec	19 sec	20 sec	17 sec
First output speed (colour):	7.6 secs	7.5 secs	7.1 sec	7.1 sec	5.7 sec	4.5 sec
First output speed (B/W):	5.4 secs	5.3 secs	4.6 sec	4.6 sec	4.0 sec	3.1 sec
Continuous output speed (colour):	20ppm	25ppm	30 ppm	35 ppm	45 ppm	55 ppm
Continuous output speed (B/W):	20ppm	25ppm	30 ppm	35 ppm	45 ppm	55 ppm
Memory Standard:	1.5 GB (2 GB Max)	1.5 GB (2 GB Max)	1.5 GB (2 GB Max)	1.5 GB (2 GB Max)	2 GB	2 GB
Memory HDD:	250 GB	250 GB	250 GB	250 GB	250 GB	250 GB
Dimensions (W x D x H):	668 x 738 x 1,155 mm*	668 x 738 x 1,155 mm*	668 x 738 x 1,155 mm*	668 x 738 x 1,155 mm*	668 x 738 x 1,205 mm*	668 x 738 x 1,205 mm*
* with 2-tray paper bank and document feeder (DF)						
* DF is optional on MP C2003SP, MP C2503SP. Height 1,030 mm without DF						
Weight:	81 kg	81 kg	85 kg	85 kg	86 kg	86.5 kg
Power source:	220-240 V, 50/60 Hz	220-240 V, 50/60 Hz	220-240 V, 50/60 Hz	220-240 V, 50/60 Hz	220-240 V, 50/60 Hz	220-240 V, 50/60 Hz
<b>COPIER</b>						
Copying process:	Dry electrostatic transfer system					
Multiple copying:	Up to 999 copies					
Resolution:	600 dpi (4 bit)					
Zoom:	From 25% to 400% in 1% steps.					
<b>PRINTER</b>						
Printer Language:	Standard: PCL5c, PCL6, PDF direct print, MediaPrint (JPEG/TIFF) Option: Adobe-Postscript-3™, IPDS (Excludes 20/25 ppm models), PictBridge					
Print resolution:	Maximum: 1,200 x 1,200 dpi					
Interface:	Standard: USB 2.0, SD slot, Ethernet 10 base-T/100 base-TX, Ethernet 1000 Base-T Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth					
Network protocol:	Standard: TCP/IP (IP v4, IP v6). Option: IPX/SPX					
Windows-environments:	Windows-5, Windows-XP, Windows-Vista, Windows-7, Windows-8, Windows-Server 2003, Windows-Server 2003R2, Windows-Server 2008, Windows-Server 2008R2, Windows-Server 2012					
Mac OS environments:	Macintosh OS X v10.2 or later					
UNIX environments:	UNIX Sun-Solaris, HP-UX, SCO OpenServer, Redhat-Linux, IBM-AIX, IBM-System i5™ HPT					
Novell-Netware-environments:	v6.5					
SAP-R/3-environments:	SAP-R/3-					
Other supported environments:	NDPS Gateway, AS/400-using OS/400 Host Print Transform					
<b>SCANNER</b>						
Scanning speed:	ARDF (optional)	ARDF (optional)	ARDF	ARDF	SPDF	SPDF
Full colour:		54 originals per minute		80 originals per minute		110 Simplex/180 Duplex
B/W:		54 originals per minute		80 originals per minute		110 Simplex/180 Duplex
Resolution:				Maximum: 1,200 dpi		
Original size:				A3, A4, A5		
File format:	Single page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF-A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi Page PDF-A					
Bundled drivers:	Network TWAIN					
Scan to:	Email: SMTP, POP, IMAP4					
Folder:	SMB, FTP, NCP					
Scanner options:	OCR Unit (searchable PDF)					
FAX (Optional):						
Circuit:	PSTN, PBX					
Compatibility:	ITU-T (CCITT) G3					
Resolution:	Standard: 8 x 3.85 line/mm, 200 x 100 dpi, 8 x 7.7 line/mm, 200 x 200 dpi					
Option:	8 x 15.4 line/mm, 400 x 400 dpi, 16 x 15.4 line/mm, 400 x 400 dpi					
Transmission speed:						
Modem speed:	G3: 2 second(s)					
Scanning speed:	Maximum: 33.6 Kbps					
Memory capacity:	1 second(s)					
Fax options:	Standard: 4 MB, Maximum: 28 MB					
PAPER HANDLING	Fax connection unit, G3 additional lines (Max 2 extra lines)					
Recommended paper size:	SRA3, A3, A4, A5, A6, B4, B5, B6					
Paper input capacity:	Maximum: 2,300 sheets					
Paper output capacity:	Maximum: 625 sheets					
Paper weight:	Maximum: 4,700 sheets					
ECOLOGY	Maximum: 3,625 sheets					
	52 – 300 gsm					

<b>Power consumption</b>		Maximum 1,470 W		Maximum 1,700 W		Maximum 1,850 W	
- Ready mode	57 W	57 W	64 W	64 W	110 W	110 W	110 W
- Sleep mode		Less than 1 W		Less than 1 W		1 W	
<b>TEC (Typical Electricity Consumption)</b>	701	889	1,175	1,340	1,927	2,664	2,870 W/h
<b>SOFTWARE</b>	SmartDeviceMonitor, Web SmartDeviceMonitor, Web Image Monitor						
- Standard OPTIONS							
Internal shift tray	✓	✓	✓	✓	✓	✓	✓
Internal 250 sheet stapleless	✓	✓	X	X	X	X	X
Internal finisher 500 sheet	✓	✓	✓	✓	✓	✓	X
1,000 sheet Finisher	X	X	✓	✓	✓	✓	✓
3,000 sheet Finisher	X	X	X	X	✓	✓	✓
1,000 sheet Booklet Finisher	X	X	✓	✓	✓	✓	✓
2,000 sheet Booklet Finisher	X	X	X	X	✓	✓	✓

**FIERY CONTROLLER E-22C\***

<b>Controller Type:</b>	Embedded Type
<b>Fiery Platform:</b>	FS100
<b>CPU:</b>	Intel Processor G850 2.9GHz
<b>Memory:</b>	2 GB
<b>Internal HDD:</b>	500 GB
<b>Operating System:</b>	Linux
<b>Network Protocol:</b>	TCP/IP (IPv4/IPv6), SMB, Bonjour
<b>Printer Description Language:</b>	Standard: PostScript 3 & PCL6/Sc
<b>Max Print Resolution:</b>	Up to 1200 dpi (2 bit)
<b>Max Scan Resolution:</b>	Up to 600 dpi
<b>Fonts:</b>	PS3: 138 fonts/PCL: 81 AGFA fonts
<b>Utilities:</b>	Standard: Command WorkStation 5, Fiery Scan, Printer Delete Utility, Fiery Web Tools, Fiery Bridge, Secure Erase and Fiery VUE

Optional: Fiery Impose, Fiery Compose, Fiery Auto Trap, EFI Spot-On

\*Not compatible with MP C2003SP, MP C2503SP